

**NDAA**  
COMPLIANT PRODUCT


**STAR-LIGHT PLUS**  
Color in Darkness Technology

**H.265**  
H.264/MJPEG

**30fps**



**5MP**  
Resolution



**5 YEAR**  
Warranty

## Summary

This NDAA-compliant MEGApix® Pano 5MP 360° view fisheye IP camera with IR can monitor an entire area with a 1.55mm fisheye lens, edge-to-edge image clarity and 5MP images at real-time 30fps, providing ultimate ROI. Star-Light Plus™ color in near-total darkness technology ensures quality video in any lighting condition. The camera also offers simultaneous H.265/H.264/MJPEG support in an IP66 vandal-resistant, discrete housing. The camera is optimized to work with the DW Spectrum® IPVMS instant dewarping feature.

## Features

- 5MP 1/1.8" image sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- Support 360° hemispheric fisheye view and 360°, 180° and 90° panoramic view
- Edge-to-edge image clarity
- 1.5mm fisheye lens
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 360° 80' Smart IR™ with intelligent camera sync.
- Smart DNR™ 3D digital noise reduction
- True day/night with mechanical IR cut filter
- Auto gain control (AGC)
- Backlight compensation (BLC)
- Auto white balance (AWB)
- Motion detection
- Two-way audio
- Micro SD/SDHC class 10 card slot (card not included)
- Web server built-in
- PoE class 3 and DC12V
- UL listed
- NDAA compliant
- IP66 environmental-rated dust-tight and water-resistant
- IK 9-rated impact-resistant
- 5 year warranty



## Accessories (Optional)



DWC-V1CNMW  
Corner mount



DWC-VFCMW  
Ceiling mount bracket





DWC-VFJUNCW  
Junction box



DWC-VFWMW  
Wall mount bracket

## Dimensions

Unit: Inch (mm)



## Specifications



<b>IMAGE</b>	
Image sensor	6.4MP 1/1.8" CMOS
Total pixels	3096 (H) X 2080 (V)
Minimum scene illumination	0.39 lux (color), 0 lux (B/W)
Maximum resolution	5MP (2592 x 1944)
<b>LENS</b>	
Focal length	1.55mm, F2.5
Lens type	Fisheye lens
HFOV / VFOV	185° / 185°
IR distance	80ft range
<b>I/O</b>	
Audio in / out and compression	1 (1.0Vms, 3K ohm) / 1, G.711
<b>OPERATIONAL</b>	
Intelligent Video Analytics	I/A: intrusion, line crossing, counting line, loitering, enter, exit, tamper (DWC-PVF5Di1TW) I/A+: object removed, tailgating, direction, stopped, appear, disappear, object left, logical rules (DWC-PPVF5Di1TW)
Shutter mode	Auto, manual, anti-flicker, slow shutter
Shutter speed	1/15-1/32000
Slow Shutter	1/2, 1/3, 1/5, 1/6, 1/7.5, 1/10
Auto gain control	Auto
Day / night	Auto, day (color), night (B/W)
3D digital noise reduction	Smart DNR™ 3D-DNR
White balance	Yes
Mirror and flip	Yes
Backlight compensation (BLC)	Yes
Privacy zones	16 programmable privacy masks
Alarm notifications	Notifications via e-mail, FTP server or SD card recording
Memory slot	Micro SD / SDHC / SDXC (card not included)
<b>NETWORK</b>	
LAN	RJ45 (10/100Base-T)
Video compression type	H.265, H.264, MJPEG
Resolution	H.265, H.264: 2592x1944, 2048x1536, 1600x1200, 1280x1024, 800x600, 480x360, 320x240 MJPEG: 1280x1024, 800x600, 480x360, 320x240
Frame rate	Up to 30fps at all resolutions
Video bitrate	100Kbps - 10Mbps, multi-rate for preview and recording
Bitrate control	Multi-streaming CBR/VBR at H.265 (controllable frame rate and bandwidth)
Streaming capability	Dual-stream at different rates and resolutions
IP	IPv4, IPv6
Protocol	TCP/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3 (MIB-2), ONVIF
Security	HTTPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
ONVIF conformance	Yes
Web viewer	OS: Windows®, Mac® OS, Linux® Browser: IE®, Google Chrome®, Mozilla Firefox®, Safari® NOTE: Chrome browser is recommended for I/A configuration
Video management software	DW Spectrum® IPVMS
<b>ENVIRONMENTAL</b>	
Operating temperature	-4°F - 122°F (-20°C - 50°C)
Operating humidity	Less than 90% (non-condensing)
IP and IK rating	IP66-rated, IK9-impact resistant
Other certifications	UL listed, CE, FCC, RoHS
<b>ELECTRICAL</b>	
Power requirement	DC12V, PoE IEEE 802.3af Class3. (Adapter not included)
Power consumption	DC12V: max 7.5W, PoE: max 8.7W
<b>MECHANICAL</b>	
Material	Aluminum vandal fisheye housing
Dimensions	4.9" x 1.88" (125 x 48mm)
Weight	1.1 lbs (0.5kg)
Warranty	5 year warranty



Built for Users.™

